



GTK::V3::Gtk::GtkAboutDialog

GtkAboutDialog — Display information about an application

Table of Contents

1	Synopsis
2	Methods
2.1	new
2.2	gtk_about_dialog_new
2.3	[gtk_about_dialog_] get_program_name
2.4	[gtk_about_dialog_] set_program_name
2.5	[gtk_about_dialog_] get_version
2.6	[gtk_about_dialog_] set_version
2.7	[gtk_about_dialog_] get_copyright
2.8	[gtk_about_dialog_] set_copyright
2.9	[gtk_about_dialog_] get_comments
2.10	[gtk_about_dialog_] set_comments
2.11	[gtk_about_dialog_] get_license
2.12	[gtk_about_dialog_] set_license
2.13	[gtk_about_dialog_] get_wrap_license
2.14	[gtk_about_dialog_] set_wrap_license
2.15	[gtk_about_dialog_] get_license_type
2.16	[gtk_about_dialog_] set_license_type
2.17	[gtk_about_dialog_] get_website
2.18	[gtk_about_dialog_] set_website
2.19	[gtk_about_dialog_] get_website_label
2.20	[gtk_about_dialog_] set_website_label
2.21	[gtk_about_dialog_] get_authors
2.22	[gtk_about_dialog_] set_authors
2.23	[gtk_about_dialog_] get_artists
2.24	[gtk_about_dialog_] set_artists
2.25	[gtk_about_dialog_] get_documenters
2.26	[gtk_about_dialog_] set_documenters
2.27	[gtk_about_dialog_] get_translator_credits
2.28	[gtk_about_dialog_] set_translator_credits
2.29	[gtk_about_dialog_] get_logo
2.30	[gtk_about_dialog_] set_logo

- 2.31 [\[gtk_about_dialog_\] get_logo_icon_name](#)
- 2.32 [\[gtk_about_dialog_\] set_logo_icon_name](#)
- 2.33 [\[gtk_about_dialog_\] add_credit_section](#)
- 3 [Types](#)
- 3.1 [enum GtkLicense](#)
- 4 [Signals](#)
- 4.1 [Not yet supported signals](#)
- 4.1.1 [activate-link](#)

```
unit class GTK::V3::Gtk::GtkAboutDialog;  
also is GTK::V3::Gtk::GtkDialog;
```

Synopsis

```
my GTK::V3::Gtk::GtkAboutDialog $about .= new(:empty);  
$about.set-program-name('My-First-GTK-Program');  
  
# Show the dialog. The status can be tested for which button was pressed  
my Int $return-status = $about.gtk-dialog-run;  
  
# When dialog buttons are pressed control returns here.  
# Hide the dialog again.  
$about.gtk-widget-hide;
```

Methods

new

```
multi method new ( Bool :$empty! )
```

Create an empty about dialog

```
multi method new ( :$widget! )
```

Create an about dialog using a native object from elsewhere. See also `Gtk::V3::Glib::GObject`.

```
multi method new ( Str :$build-id! )
```

Create an about dialog using a native object from a builder. See also `Gtk::V3::Glib::GObject`.

gtk_about_dialog_new

```
method gtk_about_dialog_new ( --> N-GObject )
```

Creates a new empty about dialog widget. See also [gnome developer docs](#). Better, shorter and easier is to use `.new(:empty)`. See info for `new()`.

[gtk_about_dialog_] get_program_name

```
method gtk_about_dialog_get_program_name ( --> Str )
```

Get the program name from the dialog. See also [gnome developer docs](#).

[gtk_about_dialog_] set_program_name

```
method gtk_about_dialog_set_program_name ( Str $pname )
```

Set the program name in the about dialog. See also [gnome developer docs](#).

[gtk_about_dialog_] get_version

```
method gtk_about_dialog_get_version ( --> Str )
```

Get the version. See also [gnome developer docs](#).

[gtk_about_dialog_] set_version

```
method gtk_about_dialog_set_version ( Str $version )
```

Set version. See also [gnome developer docs](#).

[gtk_about_dialog_] get_copyright

```
method gtk_about_dialog_get_copyright
```

Get copyright. See also [gnome developer docs](#).

[gtk_about_dialog_] set_copyright

```
method gtk_about_dialog_set_copyright
```

Set copyright. See also [gnome developer docs](#).

[gtk_about_dialog_] get_comments

```
method gtk_about_dialog_get_comments
```

Get comments. See also [gnome developer docs](#).

[gtk_about_dialog_] set_comments

```
method gtk_about_dialog_set_comments
```

Set comments. See also [gnome developer docs](#).

[gtk_about_dialog_] get_license

```
method gtk_about_dialog_get_license
```

Get license. See also [gnome developer docs](#).

[gtk_about_dialog_] set_license

```
method gtk_about_dialog_set_license
```

Set license. See also [gnome developer docs](#).

[gtk_about_dialog_] get_wrap_license

```
method gtk_about_dialog_get_wrap_license
```

Return 1 if license is wrapped. See also [gnome developer docs](#).

[gtk_about_dialog_] set_wrap_license

```
method gtk_about_dialog_set_wrap_license
```

Sets whether the license text in about is automatically wrapped. See also [gnome developer docs](#).

[gtk_about_dialog_] get_license_type

```
method gtk_about_dialog_get_license_type
```

Get license type. This is an integer representing GtkLicense described above. Example;

```
my Int $lt = $dialog.get_license_type;  
say "License type: ", GtkLicense($lt);
```

See also [gnome developer docs](#).

[gtk_about_dialog_] set_license_type

```
method gtk_about_dialog_set_license_type
```

Set license type. E.g.

```
$dialog.set_license_type(GTK_LICENSE_ARTISTIC);
```

See also [gnome developer docs](#).

[gtk_about_dialog_] get_website

```
method gtk_about_dialog_get_website
```

Get website. See also [gnome developer docs](#).

[gtk_about_dialog_] set_website

```
method gtk_about_dialog_set_website
```

Set website. See also [gnome developer docs](#).

[gtk_about_dialog_] get_website_label

```
method gtk_about_dialog_get_website_label
```

Returns the label used for the website link. See also [gnome developer docs](#).

[gtk_about_dialog_] set_website_label

```
method gtk_about_dialog_set_website_label
```

Set website label. See also [gnome developer docs](#).

[gtk_about_dialog_] get_authors

```
method gtk_about_dialog_get_authors
```

Get list of authors. See also [gnome developer docs](#).

[gtk_about_dialog_] set_authors

```
method gtk_about_dialog_set_authors
```

Set authors. See also [gnome developer docs](#).

[gtk_about_dialog_] get_artists

```
method gtk_about_dialog_get_artists
```

Get artists. See also [gnome developer docs](#).

[gtk_about_dialog_] set_artists

```
method gtk_about_dialog_set_artists
```

Set artists. See also [gnome developer docs](#).

[gtk_about_dialog_] get_documenters

```
method gtk_about_dialog_get_documenters
```

Get documenters. See also [gnome developer docs](#).

[gtk_about_dialog_] set_documenters

```
method gtk_about_dialog_set_documenters
```

Set documenters. See also [gnome developer docs](#).

[gtk_about_dialog_] get_translator_credits

```
method gtk_about_dialog_get_translator_credits
```

Get translator credits See also [gnome developer docs](#).

[gtk_about_dialog_] set_translator_credits

```
method gtk_about_dialog_set_translator_credits
```

Set translator credits See also [gnome developer docs](#).

[gtk_about_dialog_] get_logo

```
method gtk_about_dialog_get_logo
```

Get pixel buffer of logo. See also [gnome developer docs](#).

[gtk_about_dialog_] set_logo

```
method gtk_about_dialog_set_logo ( OpaquePointer $logo-pixbuf )
```

Set the logo from a pixel buffer. E.g.

```
my GTK::V3::Gtk::GtkImage $logo .= new(  
  :filename(%?RESOURCES<library-logo.png>.Str)  
) ;  
$about-dialog.set-logo($logo.get-pixbuf);
```

See also [gnome developer docs](#).

[gtk_about_dialog_] get_logo_icon_name

```
method gtk_about_dialog_get_logo_icon_name
```

Get name of logo icon. See also [gnome developer docs](#).

[gtk_about_dialog_] set_logo_icon_name

```
method gtk_about_dialog_set_logo_icon_name
```

Set name of logo icon. See also [gnome developer docs](#).

[gtk_about_dialog_] add_credit_section

```
method gtk_about_dialog_add_credit_section
```

Add credit section. See also [gnome developer docs](#).

Types

enum GtkLicense

A series of names to set the license type.

- `GTK_LICENSE_UNKNOWN`; No license specified
- `GTK_LICENSE_CUSTOM`; A license text is going to be specified by the developer
- `GTK_LICENSE_GPL_2_0`; The GNU General Public License, version 2.0 or later
- `GTK_LICENSE_GPL_3_0`; The GNU General Public License, version 3.0 or later
- `GTK_LICENSE_LGPL_2_1`; The GNU Lesser General Public License, version 2.1 or later
- `GTK_LICENSE_LGPL_3_0`; The GNU Lesser General Public License, version 3.0 or later
- `GTK_LICENSE_BSD`; The BSD standard license
- `GTK_LICENSE_MIT_X11`; The MIT/X11 standard license
- `GTK_LICENSE_ARTISTIC`; The Artistic License, version 2.0
- `GTK_LICENSE_GPL_2_0_ONLY`; The GNU General Public License, version 2.0 only. Since 3.12.
- `GTK_LICENSE_GPL_3_0_ONLY`; The GNU General Public License, version 3.0 only. Since 3.12.
- `GTK_LICENSE_LGPL_2_1_ONLY`; The GNU Lesser General Public License, version 2.1 only. Since 3.12.
- `GTK_LICENSE_LGPL_3_0_ONLY`; The GNU Lesser General Public License, version 3.0 only. Since 3.12.
- `GTK_LICENSE_AGPL_3_0`; The GNU Affero General Public License, version 3.0 or later. Since: 3.22.
- `GTK_LICENSE_AGPL_3_0_ONLY`; The GNU Affero General Public License, version 3.0 only. Since: 3.22.27.

See `gtk_about_dialog_get_license_type` for an example.

Signals

Not yet supported signals

activate-link

The signal which gets emitted to activate a URI. Applications may connect to it to override the default behaviour, which is to call `gtk_show_uri_on_window()`.