

Internet Engineering Task Force (IETF)
Request for Comments: 7468
Category: Standards Track
ISSN: 2070-1721

S. Josefsson
SJD AB
S. Leonard
Penango, Inc.
April 2015

Textual Encodings of PKIX, PKCS, and CMS Structures

Abstract

This document describes and discusses the textual encodings of the Public-Key Infrastructure X.509 (PKIX), Public-Key Cryptography Standards (PKCS), and Cryptographic Message Syntax (CMS). The textual encodings are well-known, are implemented by several applications and libraries, and are widely deployed. This document articulates the de facto rules by which existing implementations operate and defines them so that future implementations can interoperate.

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc7468>.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	General Considerations	3
3.	ABNF	5
4.	Guide	7
5.	Textual Encoding of Certificates	8
5.1.	Encoding	8
5.2.	Explanatory Text	9
5.3.	File Extension	9
6.	Textual Encoding of Certificate Revocation Lists	10
7.	Textual Encoding of PKCS #10 Certification Request Syntax	11
8.	Textual Encoding of PKCS #7 Cryptographic Message Syntax	11
9.	Textual Encoding of Cryptographic Message Syntax	12
10.	One Asymmetric Key and the Textual Encoding of PKCS #8 Private Key Info	12
11.	Textual Encoding of PKCS #8 Encrypted Private Key Info	13
12.	Textual Encoding of Attribute Certificates	13
13.	Textual Encoding of Subject Public Key Info	14
14.	Security Considerations	14
15.	References	14
15.1.	Normative References	14
15.2.	Informative References	15
Appendix A.	Non-conforming Examples	17
Appendix B.	DER Expectations	18
Acknowledgements	19
Authors' Addresses	20

1. Introduction

Several security-related standards used on the Internet define ASN.1 data formats that are normally encoded using the Basic Encoding Rules (BER) or Distinguished Encoding Rules (DER) [X.690], which are binary, octet-oriented encodings. This document is about the textual encodings of the following formats:

1. Certificates, Certificate Revocation Lists (CRLs), and Subject Public Key Info structures in the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile [RFC5280].
2. PKCS #10: Certification Request Syntax [RFC2986].
3. PKCS #7: Cryptographic Message Syntax [RFC2315].
4. Cryptographic Message Syntax [RFC5652].

5. PKCS #8: Private-Key Information Syntax [RFC5208], renamed to One Asymmetric Key in Asymmetric Key Package [RFC5958], and Encrypted Private-Key Information Syntax in the same documents.
6. Attribute Certificates in An Internet Attribute Certificate Profile for Authorization [RFC5755].

A disadvantage of a binary data format is that it cannot be interchanged in textual transports, such as email or text documents. One advantage with text-based encodings is that they are easy to modify using common text editors; for example, a user may concatenate several certificates to form a certificate chain with copy-and-paste operations.

The tradition within the RFC series can be traced back to Privacy-Enhanced Mail (PEM) [RFC1421], based on a proposal by Marshall Rose in Message Encapsulation [RFC934]. Originally called "PEM encapsulation mechanism", "encapsulated PEM message", or (arguably) "PEM printable encoding", today the format is sometimes referred to as "PEM encoding". Variations include OpenPGP ASCII armor [RFC4880] and OpenSSH key file format [RFC4716].

For reasons that basically boil down to non-coordination or inattention, many PKIX, PKCS, and CMS libraries implement a text-based encoding that is similar to -- but not identical with -- PEM encoding. This document specifies the `_textual encoding_ format`, articulates the de facto rules that most implementations operate by, and provides recommendations that will promote interoperability going forward. This document also provides common nomenclature for syntax elements, reflecting the evolution of this de facto standard format. Peter Gutmann's "X.509 Style Guide" [X.509SG] contains a section "base64 Encoding" that describes the formats and contains suggestions similar to what is in this document. All figures are real, functional examples, with key lengths and inner contents chosen to be as small as practicable.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

2. General Considerations

Textual encoding begins with a line comprising "-----BEGIN ", a label, and "-----", and ends with a line comprising "-----END ", a label, and "-----". Between these lines, or "encapsulation boundaries", are base64-encoded data according to Section 4 of [RFC4648]. (PEM [RFC1421] referred to this data as the "encapsulated

text portion".) Data before the encapsulation boundaries are permitted, and parsers MUST NOT malfunction when processing such data. Furthermore, parsers SHOULD ignore whitespace and other non-base64 characters and MUST handle different newline conventions.

The type of data encoded is labeled depending on the type label in the "-----BEGIN " line (pre-encapsulation boundary). For example, the line may be "-----BEGIN CERTIFICATE-----" to indicate that the content is a PKIX certificate (see further below). Generators MUST put the same label on the "-----END " line (post-encapsulation boundary) as the corresponding "-----BEGIN " line. Labels are formally case-sensitive, uppercase, and comprised of zero or more characters; they do not contain consecutive spaces or hyphen-minuses, nor do they contain spaces or hyphen-minuses at either end. Parsers MAY disregard the label in the post-encapsulation boundary instead of signaling an error if there is a label mismatch: some extant implementations require the labels to match; others do not.

There is exactly one space character (SP) separating the "BEGIN" or "END" from the label. There are exactly five hyphen-minus (also known as dash) characters ("-") on both ends of the encapsulation boundaries, no more, no less.

The label type implies that the encoded data follows the specified syntax. Parsers MUST handle non-conforming data gracefully. However, not all parsers or generators prior to this document behave consistently. A conforming parser MAY interpret the contents as another label type but ought to be aware of the security implications discussed in the Security Considerations section. The labels described in this document identify container formats that are not specific to any particular cryptographic algorithm, a property consistent with algorithm agility. These formats use the ASN.1 AlgorithmIdentifier structure as described in Section 4.1.1.2 of [RFC5280].

Unlike legacy PEM encoding [RFC1421], OpenPGP ASCII armor, and the OpenSSH key file format, textual encoding does *not* define or permit headers to be encoded alongside the data. Empty space can appear between the pre-encapsulation boundary and the base64, but generators SHOULD NOT emit such any such spacing. (The provision for this empty area is a throwback to PEM, which defined an "encapsulated header portion".)

Implementers need to be aware that extant parsers diverge considerably on the handling of whitespace. In this document, "whitespace" means any character or series of characters that represent horizontal or vertical space in typography. In US-ASCII, whitespace means HT (0x09), VT (0x0B), FF (0x0C), SP (0x20), CR

(0x0D), and LF (0x0A); "blank" means HT and SP; lines are divided with CRLF, CR, or LF. The common ABNF production WSP is congruent with "blank"; a new production W is used for "whitespace". The ABNF in Section 3 is specific to US-ASCII. As these textual encodings can be used on many different systems as well as on long-term archival storage media such as paper or engravings, an implementer ought to use the spirit rather than the letter of the rules when generating or parsing these formats in environments that are not strictly limited to US-ASCII.

Most extant parsers ignore blanks at the ends of lines; blanks at the beginnings of lines or in the middle of the base64-encoded data are far less compatible. These observations are codified in Figure 1. The most lax parser implementations are not line-oriented at all and will accept any mixture of whitespace outside of the encapsulation boundaries (see Figure 2). Such lax parsing may run the risk of accepting text that was not intended to be accepted in the first place (e.g., because the text was a snippet or sample).

Generators MUST wrap the base64-encoded lines so that each line consists of exactly 64 characters except for the final line, which will encode the remainder of the data (within the 64-character line boundary), and they MUST NOT emit extraneous whitespace. Parsers MAY handle other line sizes. These requirements are consistent with PEM [RFC1421].

Files MAY contain multiple textual encoding instances. This is used, for example, when a file contains several certificates. Whether the instances are ordered or unordered depends on the context.

3. ABNF

The ABNF [RFC5234] of the textual encoding is:

```

textualmsg = preeb *WSP eol
            *eolWSP
            base64text
            posteb *WSP [eol]

preeb      = "-----BEGIN " label "-----" ; unlike [RFC1421] (A)BNF,
            ; eol is not required (but
posteb     = "-----END " label "-----"   ; see [RFC1421], Section 4.4)

base64char = ALPHA / DIGIT / "+" / "/"

base64pad  = "="

base64line = 1*base64char *WSP eol

```

```

base64finl = *base64char (base64pad *WSP eol base64pad /
                        *2base64pad) *WSP eol
            ; ...AB= <EOL> = <EOL> is not good, but is valid

base64text = *base64line base64finl
            ; we could also use <enclbinbody> from RFC 1421, which requires
            ; 16 groups of 4 chars, which means exactly 64 chars per
            ; line, except the final line, but this is more accurate

labelchar  = %x21-2C / %x2E-7E      ; any printable character,
            ; except hyphen-minus

label      = [ labelchar *( ["-" / SP] labelchar ) ]      ; empty ok

eol        = CRLF / CR / LF

eolWSP     = WSP / CR / LF                ; compare with LWSP

```

Figure 1: ABNF (Standard)

```

laxtextualmsg = *W preeb
               laxbase64text
               posteb *W

W              = WSP / CR / LF / %x0B / %x0C                ; whitespace

laxbase64text = *(W / base64char) [base64pad *W [base64pad *W]]

```

Figure 2: ABNF (Lax)

```

stricttextualmsg = preeb eol
                  strictbase64text
                  posteb eol

strictbase64finl = *15(4base64char) (4base64char / 3base64char
                                   base64pad / 2base64char 2base64pad) eol

base64fullline  = 64base64char eol

strictbase64text = *base64fullline strictbase64finl

```

Figure 3: ABNF (Strict)

New implementations SHOULD emit the strict format (Figure 3) specified above. The choice of parsing strategy depends on the context of use.

4. Guide

For convenience, these figures summarize the structures, encodings, and references in the following sections:

Sec.	Label	ASN.1 Type	Reference	Module
5	CERTIFICATE	Certificate	[RFC5280]	id-pkix1-e
6	X509 CRL	CertificateList	[RFC5280]	id-pkix1-e
7	CERTIFICATE REQUEST	CertificationRequest	[RFC2986]	id-pkcs10
8	PKCS7	ContentInfo	[RFC2315]	id-pkcs7*
9	CMS	ContentInfo	[RFC5652]	id-cms2004
10	PRIVATE KEY	PrivateKeyInfo ::= OneAsymmetricKey	[RFC5208] [RFC5958]	id-pkcs8 id-aKPV1
11	ENCRYPTED PRIVATE KEY	EncryptedPrivateKeyInfo	[RFC5958]	id-aKPV1
12	ATTRIBUTE CERTIFICATE	AttributeCertificate	[RFC5755]	id-acv2
13	PUBLIC KEY	SubjectPublicKeyInfo	[RFC5280]	id-pkix1-e

Figure 4: Convenience Guide

```

-----
id-pkixmod OBJECT IDENTIFIER ::= {iso(1) identified-organization(3)
    dod(6) internet(1) security(5) mechanisms(5) pkix(7) mod(0)}
id-pkix1-e OBJECT IDENTIFIER ::= {id-pkixmod pkix1-explicit(18)}
id-acv2 OBJECT IDENTIFIER ::= {id-pkixmod mod-attribute-cert-v2(61)}
id-pkcs OBJECT IDENTIFIER ::= {iso(1) member-body(2) us(840)
    rsadsi(113549) pkcs(1)}
id-pkcs10 OBJECT IDENTIFIER ::= {id-pkcs 10 modules(1) pkcs-10(1)}
id-pkcs7 OBJECT IDENTIFIER ::= {id-pkcs 7 modules(0) pkcs-7(1)}
id-pkcs8 OBJECT IDENTIFIER ::= {id-pkcs 8 modules(1) pkcs-8(1)}
id-sm-mod OBJECT IDENTIFIER ::= {id-pkcs 9 smime(16) modules(0)}
id-aKPV1 OBJECT IDENTIFIER ::= {id-sm-mod mod-asymmetricKeyPkgV1(50)}
id-cms2004 OBJECT IDENTIFIER ::= {id-sm-mod cms-2004(24)}

```

* This OID does not actually appear in PKCS #7 v1.5 [RFC2315]. It was defined in the ASN.1 module to PKCS #7 v1.6 [P7v1.6], and has been carried forward through PKCS #12 [RFC7292].

Figure 5: ASN.1 Module Object Identifier Value Assignments

5. Textual Encoding of Certificates

5.1. Encoding

Public-key certificates are encoded using the "CERTIFICATE" label. The encoded data MUST be a BER (DER strongly preferred; see Appendix B) encoded ASN.1 Certificate structure as described in Section 4 of [RFC5280].

-----BEGIN CERTIFICATE-----
MIICLDCCAdKgAwIBAgIBADAKBggqhkJOPQQDAjB9MQswCQYDVQQGEwJCRTEPMA0G
A1UEChMGR251VExTMSUwIwYDVQQLEExxHbnVUTFMgY2VydGhmaWNhdGUgYXV0aG9y
aXR5MQ8wDQYDVQQIEwZMZXV2ZW4xJTAjBgNVBAMTHEdudVRMUyBjZXJ0aWZpY2F0
ZSBhdXRob3JpdHkwHhcNMTEwNTIzMjAzODIxWhcNMTEwMjIyMDc0MTUxWjB9MQsw
CQYDVQQGEwJCRTEPMA0GA1UEChMGR251VExTMSUwIwYDVQQLEExxHbnVUTFMgY2Vy
dGhmaWNhdGUgYXV0aG9yaXR5MQ8wDQYDVQQIEwZMZXV2ZW4xJTAjBgNVBAMTHEdu
dVRMUyBjZXJ0aWZpY2F0ZSBhdXRob3JpdHkwWTATBgqhkJOPQIBBggqhkJOPQMB
BwNCAARS2I0jiuNn14Y2sSALCX3IybqiIUvXUpj+oNfzngvj/Niyv2394BwnW4X
uQ4RTEiywK87WRcWMGgJB5kX/t2no0MwQTAPBgNVHRMBAf8EBTADAQH/MA8GA1Ud
DwEB/wQFAwMHBGAWHQYDVR0OBByEFPC0gf6YEr+1KLlkQAPLzB9mTigDMAoGCCqG
SM49BAMCA0gAMEUCIDGuwDlKPyG+hRf88MeyMQcqOFZD0TbVleF+UsAGQ4enAiEA
l4wOuDwKQa+upc8GftXE2C//4mKANBC6It0lgUaTIpo=
-----END CERTIFICATE-----

Figure 6: Certificate Example

Historically, the label "X509 CERTIFICATE" and also less commonly "X.509 CERTIFICATE" have been used. Generators conforming to this document MUST generate "CERTIFICATE" labels and MUST NOT generate "X509 CERTIFICATE" or "X.509 CERTIFICATE" labels. Parsers SHOULD NOT treat "X509 CERTIFICATE" or "X.509 CERTIFICATE" as equivalent to "CERTIFICATE", but a valid exception may be for backwards compatibility (potentially together with a warning).

5.2. Explanatory Text

Many tools are known to emit explanatory text before the BEGIN and after the END lines for PKIX certificates, more than any other type. If emitted, such text SHOULD be related to the certificate, such as providing a textual representation of key data elements in the certificate.

```
Subject: CN=Atlantis
Issuer: CN=Atlantis
Validity: from 7/9/2012 3:10:38 AM UTC to 7/9/2013 3:10:37 AM UTC
-----BEGIN CERTIFICATE-----
MIIBmTCCAUEgAwIBAgIBKjAJBgUrDgMCHQUAMBMxETAPBgNVBAMTCEF0bGFudGlx
MB4XDTEyMDcwOTAzMTAzOFoXDTEzMDcwOTAzMTAzNlowEzERMA8GA1UEAxMIQXR5
YW50aXMwXDNANBgkqhkiG9w0BAQEFAANLADBIAGkEAg+BxO+miabDIHHx+yquqzqNh
Ryn/XtkJIIHvcYtHvIX+S1x5ErgMoHehycpoxbErZmVR4GCq1S2diNmRFZCrtQID
AQABo4GJMIGMAwGAlUdEwEB/wQCMAAwIAYDVR0EAQH/BBYwFDAOMAwGCisGAQQB
gjcCARUDAgeAMB0GAlUdJQQWMBQGCCsGAQUFBwMCEBggrBgEFBQcDAZAlBgNVHQEE
LjAsgBA0jOnSSuIHYmnVryHAdywMoRUwEzERMA8GA1UEAxMIQXR5YW50aXOCASow
CQYFKw4DAh0FAANBAKI6HRBaNEL5R0n56nvfclQNaXiDT174uf+lojzA4lhVInc0
ILwPnZlizL4MlI9eCSHhVQBHEp2uQdXJB+d5Byg=
-----END CERTIFICATE-----
```

Figure 7: Certificate Example with Explanatory Text

5.3. File Extension

Although textual encodings of PKIX structures can occur anywhere, many tools are known to offer an option to output this encoding when serializing PKIX structures. To promote interoperability and to separate DER encodings from textual encodings, the extension ".crt" SHOULD be used for the textual encoding of a certificate. Implementations should be aware that in spite of this recommendation, many tools still default to encode certificates in this textual encoding with the extension ".cer".

This section does not disturb the official application/pkix-cert registration [RFC2585] in any way (which states that "each '.cer' file contains exactly one certificate, encoded in DER format"), but merely articulates a widespread, de facto alternative.

6. Textual Encoding of Certificate Revocation Lists

Certificate Revocation Lists (CRLs) are encoded using the "X509 CRL" label. The encoded data MUST be a BER (DER strongly preferred; see Appendix B) encoded ASN.1 CertificateList structure as described in Section 5 of [RFC5280].

```
-----BEGIN X509 CRL-----
MIIB9DCCA8CAQEWcWYJKoZIhvcNAQEFMIIIBCEDEXMBUGA1UEChMOVmVyaVNpZ24s
IEluYy4xHzAdBgNVBAsTF1Zlcm1TaWduIFRydXN0IE5ldHdvcm5xRjBEBGNVBAsT
PXd3dy52ZXJpc2lnbi5jb20vcnVwb3NpdG9yeS9SUEEgSW5jb3JwLiBieSBSZWYu
LExJQUiUwTFREKGMpOTGxHjAcBgNVBAsTFVBlcnNvbWVyaW90IFZhbGlkYXRlZDEm
MCQGA1UECzMdRGlnaXRhbCBJRjRDbGFzcyAxIC0gTmV0c2NhcnVyaW90GDAWBgNVBAMU
D1NpbW9uIEpvc2Vmc3NvbG91eSImcGAgS1b3DQEJARYTc21tb25Aam9zZWZzc29u
Lm9yZxcnNMDYxMjI3MDgwMjM0WhcNMDcwMjA3MDgwMjM1WjAjaMCECEC4QNwPFRoWd
elUNPl1hhTgXDTA2MTIyNzA4MDIzNFowCwYJKoZIhvcNAQEFFA4GBAD0zX+J2hkcc
Nbrq1Dn5IKL8nXLgPGcHv1I/le1MNo9tlohGQxB5HnFukRPAY82fR6Epor4aHgVy
b+5y+neKN9Kn2mPF4iiun+a4o26CjJ0pArojCLlp8T0yyi9Xxvyc/ezaZ98HiIyP
c3DGMNR+oUmSjKZ0jIhAYmeLxaPHfQwR
-----END X509 CRL-----
```

Figure 8: CRL Example

Historically, the label "CRL" has rarely been used. Today, it is not common and many popular tools do not understand the label. Therefore, this document standardizes "X509 CRL" in order to promote interoperability and backwards-compatibility. Generators conforming to this document MUST generate "X509 CRL" labels and MUST NOT generate "CRL" labels. Parsers SHOULD NOT treat "CRL" as equivalent to "X509 CRL".

7. Textual Encoding of PKCS #10 Certification Request Syntax

PKCS #10 Certification Requests are encoded using the "CERTIFICATE REQUEST" label. The encoded data MUST be a BER (DER strongly preferred; see Appendix B) encoded ASN.1 CertificationRequest structure as described in [RFC2986].

```
-----BEGIN CERTIFICATE REQUEST-----
MIIBWDCCAQcCAQAwTjELMAkGA1UEBhMCU0UxJzAlBgNVBAoTHlNpbW9uIEpvc2Vm
c3NvbiBEYXRha29uc3VsdCBQjEWMBQGA1UEAxMNam9zZWZzc29uLm9yZzBOMBAG
ByqGSM49AgEGBSuBBAAhAzoABLLPSkuXY0166MbxVJ3Mot5FCFuqQfn6dTs+9/CM
E0lSwVej77tj56kj9R/j9Q+LfysX8FO9I5p3oGIwYAYJKoZIhvcNAQkOMVMwUTAY
BgNVHREETAPgg1qb3NlZnNzb24ub3JnMAwGA1UdEwEB/wQCMAAwDwYDVR0PAQH/
BAUDAwegADAWBgNVHSUBAf8EDDAKBggrBgEFBQcDATAKBggqhkJOPQDAGM/ADA8
AhxBvfhxPffBbsElNoFmCUczOFAPeUQVUw3ZP69AhwWXk3dgSUSknuwL5g/ftAY
dEQc8B8jAcnuOrfU
-----END CERTIFICATE REQUEST-----
```

Figure 9: PKCS #10 Example

The label "NEW CERTIFICATE REQUEST" is also in wide use. Generators conforming to this document MUST generate "CERTIFICATE REQUEST" labels. Parsers MAY treat "NEW CERTIFICATE REQUEST" as equivalent to "CERTIFICATE REQUEST".

8. Textual Encoding of PKCS #7 Cryptographic Message Syntax

PKCS #7 Cryptographic Message Syntax structures are encoded using the "PKCS7" label. The encoded data MUST be a BER-encoded ASN.1 ContentInfo structure as described in [RFC2315].

```
-----BEGIN PKCS7-----
MIHjBgsqhkiG9w0BCRABF6CB0zCB0AIBADFhol8CAQCgGwYJKoZIhvcNAQUUMMA4E
CLfrI6dr0gUWAgITiDAjBgsqhkiG9w0BCRADCTAUBggqhkiG9w0DBwQIZpECRWtz
u5kEGDCjerXY8odQ7EEErOmZJvAurk/j81IrozBSBgkqhkiG9w0BBwEwMwYLKoZI
hvcNAQkQAw8wJDAUBggqhkiG9w0DBwQI0tCBcU09nxEwDAYIKwYBBQUIAQIFAIQAQ
OsYGYUFdAH0RNc1p4VbKEAQUM2Xo8PMHBoYdqEcsbTodlCFAZH4=
-----END PKCS7-----
```

Figure 10: PKCS #7 Example

The label "CERTIFICATE CHAIN" has been in use to denote a degenerate PKCS #7 structure that contains only a list of certificates (see Section 9 of [RFC2315]). Several modern tools do not support this label. Generators MUST NOT generate the "CERTIFICATE CHAIN" label. Parsers SHOULD NOT treat "CERTIFICATE CHAIN" as equivalent to "PKCS7".

PKCS #7 is an old specification that has long been superseded by CMS [RFC5652]. Implementations SHOULD NOT generate PKCS #7 when CMS is an alternative.

9. Textual Encoding of Cryptographic Message Syntax

Cryptographic Message Syntax structures are encoded using the "CMS" label. The encoded data MUST be a BER-encoded ASN.1 ContentInfo structure as described in [RFC5652].

```
-----BEGIN CMS-----
MIGDBgsqhkig9w0BCRABCaB0MHICAQAwDQYLKoZIhvcNAQkQAwwXgYJKoZIhvcN
AQcBoFEET3icc87PK0nNK9ENqSxItVioSa0o0S/ISczMs1ZlzkgsKk4tsQ0NlnUM
dvv05OXi5XLPLEtViMwvLVLwSE0sKlFIVHAqSk3MBkkBAJv0Fx0=
-----END CMS-----
```

Figure 11: CMS Example

CMS is the IETF successor to PKCS #7. Section 1.1.1 of [RFC5652] describes the changes since PKCS #7 v1.5. Implementations SHOULD generate CMS when it is an alternative, promoting interoperability and forwards-compatibility.

10. One Asymmetric Key and the Textual Encoding of PKCS #8 Private Key Info

Unencrypted PKCS #8 Private Key Information Syntax structures (PrivateKeyInfo), renamed to Asymmetric Key Packages (OneAsymmetricKey), are encoded using the "PRIVATE KEY" label. The encoded data MUST be a BER (DER preferred; see Appendix B) encoded ASN.1 PrivateKeyInfo structure as described in PKCS #8 [RFC5208], or a OneAsymmetricKey structure as described in [RFC5958]. The two are semantically identical and can be distinguished by version number.

```
-----BEGIN PRIVATE KEY-----
MIGEAgEAMBAGByqGSM49AgEGBSuBBAKBG0wawIBAQQgVcB/UNPخالR9zDYAjQIf
jojUDiQuGnSjrFEEzZPT/92hRANCAAsc7UJtgnF/abqWM60T3XNJEzBv5ez9TdwK
H0M6xpM2q+53wmsN/eYldgtjgBd3DBmHtPilCkiFICXyaA8z9LkJ
-----END PRIVATE KEY-----
```

Figure 12: PKCS #8 PrivateKeyInfo (OneAsymmetricKey) Example

11. Textual Encoding of PKCS #8 Encrypted Private Key Info

Encrypted PKCS #8 Private Key Information Syntax structures (EncryptedPrivateKeyInfo), called the same in [RFC5958], are encoded using the "ENCRYPTED PRIVATE KEY" label. The encoded data MUST be a BER (DER preferred; see Appendix B) encoded ASN.1 EncryptedPrivateKeyInfo structure as described in PKCS #8 [RFC5208] and [RFC5958].

```
-----BEGIN ENCRYPTED PRIVATE KEY-----
MIHNMEAGCSqGSib3DQEFDTAzMBsGCSqGSib3DQEFDDA0BAghhICA6T/51QICCAAw
FAYIKoZIhvcNAwcECBCxDgvlI59i9BIGIY3CAqlMNBgaSI5QiiWVNJ3IpfLnEiEsW
Z0JI0HyRmKK/+cr9QPLnzxImm0TR9s4JrG3CilzTWvb0jIvbG3hu0zyFPraoMkap
8eRzWsIvC5SVel+CSj0S2mVS87cyjld+txrmrXOVYDE+eTgMLbrLmsWh3QkCTRtF
QC7k0NNzUHTV9yGDwfqMbw==
-----END ENCRYPTED PRIVATE KEY-----
```

Figure 13: PKCS #8 EncryptedPrivateKeyInfo Example

12. Textual Encoding of Attribute Certificates

Attribute certificates are encoded using the "ATTRIBUTE CERTIFICATE" label. The encoded data MUST be a BER (DER strongly preferred; see Appendix B) encoded ASN.1 AttributeCertificate structure as described in [RFC5755].

```
-----BEGIN ATTRIBUTE CERTIFICATE-----
MIICKzCCAZQCAQEwgZeggZQwgYmkgYYwgYMxCzAJBgNVBAYTAlVTMREwDwYDVQQI
DAh0ZXcgWW9yazEUMBIGAlUEBwwLU3RvbnkgQnJvb2sxZDZANBgNVBAoMBkNTRTU5
MjE6MDgGAlUEAwU2NvdHQGU3RhbGxlcj9lbWVpYmEFkZHZHJlc3M9c3N0YWxsZXJA
aWMuc3VueXNiLmVkdQIGARWrgUUSoIGMMIGJpIGMMIGDMQswCQYDVQQGEwJVUzER
MA8GAlUECAwITmV3IFlvcmsxFDASBgNVBACMC1N0b255IEJyb29rMQ8wDQYDVQQK
DAZDU0U1OTIxOjA4BGNVBAMMMVNjb3R0IFN0YWxsZXIvZW1haWxBZGRyZXNzPXNz
dGFsbGVyQGljLnN1bnlzYi5lZHUwDQYJKoZIhvcNAQEFBQACBgEVq4FFSjAiGA8z
OTA3MDIwMTAlMDAwMfoYDzM5MTEwMTMxMDUwMDAwWjArMCKGAlUYSDEiMCCGHmh0
dHA6Ly9pZGVyYXNobi5vcmcvaW5kZXguaHRtbDANBgkqhkiG9w0BAQUFAAOBgQAV
M9axFPXXozEFcer06bj9MCBCCQLtAM7ZXcZjcxxyva7xCBDmtZXPYUluHf50cWPJz
5XPus/xS9wBgtlM3fldIKNyNO8RsMp6Ocx+PGlICc7zpZiGmCYLl1641AEGPO/bsw
SmluaklaZIttePeTAHeJJs8izNJ5aR3Wcd3A5gLztQ==
-----END ATTRIBUTE CERTIFICATE-----
```

Figure 14: Attribute Certificate Example

13. Textual Encoding of Subject Public Key Info

Public keys are encoded using the "PUBLIC KEY" label. The encoded data MUST be a BER (DER preferred; see Appendix B) encoded ASN.1 SubjectPublicKeyInfo structure as described in Section 4.1.2.7 of [RFC5280].

```
-----BEGIN PUBLIC KEY-----
MHYwEAYHKoZIzj0CAQYFK4EEACIDYgAEnlLlwlN/KBYQRVH6HfIMTzfEqJOVztLe
kLchp2hi78cCaMY81FBlyS8J9l7krc+M4aBeCGYFjba+hiXttJWPL7ydlE+5UG4U
Nkn3Eos8EiZByi9DVsyfy9eejh+8AXgp
-----END PUBLIC KEY-----
```

Figure 15: Subject Public Key Info Example

14. Security Considerations

Data in this format often originates from untrusted sources, thus parsers must be prepared to handle unexpected data without causing security vulnerabilities.

Implementers building implementations that rely on canonical representation or the ability to fingerprint a particular data object need to understand that this document does not define canonical encodings. The first ambiguity is introduced by permitting the text-encoded representation instead of the binary BER or DER encodings, but further ambiguities arise when multiple labels are treated as similar. Variations of whitespace and non-base64 alphabetic characters can create further ambiguities. Data encoding ambiguities also create opportunities for side channels. If canonical encodings are desired, the encoded structure must be decoded and processed into a canonical form (namely, DER encoding).

15. References

15.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2315] Kaliski, B., "PKCS #7: Cryptographic Message Syntax Version 1.5", RFC 2315, March 1998, <<http://www.rfc-editor.org/info/rfc2315>>.
- [RFC2986] Nystrom, M. and B. Kaliski, "PKCS #10: Certification Request Syntax Specification Version 1.7", RFC 2986, November 2000, <<http://www.rfc-editor.org/info/rfc2986>>.

- [RFC4648] Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", RFC 4648, October 2006, <<http://www.rfc-editor.org/info/rfc4648>>.
- [RFC5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S., Housley, R., and W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 5280, May 2008, <<http://www.rfc-editor.org/info/rfc5280>>.
- [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <<http://www.rfc-editor.org/info/rfc5234>>.
- [RFC5652] Housley, R., "Cryptographic Message Syntax (CMS)", STD 70, RFC 5652, September 2009, <<http://www.rfc-editor.org/info/rfc5652>>.
- [RFC5755] Farrell, S., Housley, R., and S. Turner, "An Internet Attribute Certificate Profile for Authorization", RFC 5755, January 2010, <<http://www.rfc-editor.org/info/rfc5755>>.
- [RFC5958] Turner, S., "Asymmetric Key Packages", RFC 5958, August 2010, <<http://www.rfc-editor.org/info/rfc5958>>.
- [X.690] International Telecommunications Union, "Information Technology - ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)", ITU-T Recommendation X.690, ISO/IEC 8825-1:2008, November 2008.

15.2. Informative References

- [RFC934] Rose, M. and E. Stefferud, "Proposed standard for message encapsulation", RFC 934, January 1985, <<http://www.rfc-editor.org/info/rfc934>>.
- [RFC1421] Linn, J., "Privacy Enhancement for Internet Electronic Mail: Part I: Message Encryption and Authentication Procedures", RFC 1421, February 1993, <<http://www.rfc-editor.org/info/rfc1421>>.
- [RFC2585] Housley, R. and P. Hoffman, "Internet X.509 Public Key Infrastructure Operational Protocols: FTP and HTTP", RFC 2585, May 1999, <<http://www.rfc-editor.org/info/rfc2585>>.

- [RFC4716] Galbraith, J. and R. Thayer, "The Secure Shell (SSH) Public Key File Format", RFC 4716, November 2006, <<http://www.rfc-editor.org/info/rfc4716>>.
- [RFC4880] Callas, J., Donnerhacke, L., Finney, H., Shaw, D., and R. Thayer, "OpenPGP Message Format", RFC 4880, November 2007, <<http://www.rfc-editor.org/info/rfc4880>>.
- [RFC5208] Kaliski, B., "Public-Key Cryptography Standards (PKCS) #8: Private-Key Information Syntax Specification Version 1.2", RFC 5208, May 2008, <<http://www.rfc-editor.org/info/rfc5208>>.
- [RFC7292] Moriarty, K., Ed., Nystrom, M., Parkinson, S., Rusch, A., and M. Scott, "PKCS #12: Personal Information Exchange Syntax v1.1", RFC 7292, July 2014, <<http://www.rfc-editor.org/info/rfc7292>>.
- [P7v1.6] Kaliski, B. and K. Kingdon, "Extensions and Revisions to PKCS #7 (Version 1.6 Bulletin)", May 1997, <<http://www.emc.com/emc-plus/rsa-labs/standards-initiatives/pkcs-7-cryptographic-message-syntax-standar.htm>>.
- [X.509SG] Gutmann, P., "X.509 Style Guide", October 2000, <<http://www.cs.auckland.ac.nz/~pgut001/pubs/x509guide.txt>>.

Appendix A. Non-conforming Examples

This appendix contains examples for the non-recommended label variants described earlier in this document. As discussed earlier, supporting these is not required and is sometimes discouraged. Still, they can be useful for interoperability testing and for easy reference.

```
-----BEGIN X509 CERTIFICATE-----
MIIBHDCBxaADAgECAGIcxzAJBgqhkJOPQQQBMAxMjAMBGNVBAUUBVBLSVghMB4X
DTE0MDkxNDA2MTU1MFoXDTI0MDkxNDA2MTU1MFowEDEOMAwGAlUEAxQFUEtJWCeW
WTATBgqhkJOPQIBBggqhkjOPQMBBwNCAATwoQsr863QrR0PoRIYQ96H7WykDePH
Wa0eVAE24bth43wCNC+U5aZ761dhGhSSJkVWRgVH5+prLlr+nzfiq+X4oxAwDjAM
BgNVHRMBAf8EAJAAMAKGByqGSM49BAEDRWAwRAIfMdkS5F631MnWVhi7uaKJzKCs
NnY/OKgBex6MIEAv2AIhAI2GdvfL+mGvhyPZE+JxRxWChmggb5/9eHdUcmW/jkOH
-----END X509 CERTIFICATE-----
```

Figure 16: Non-standard 'X509' Certificate Example

```
-----BEGIN X.509 CERTIFICATE-----
MIIBHDCBxaADAgECAGIcxzAJBgqhkJOPQQQBMAxMjAMBGNVBAUUBVBLSVghMB4X
DTE0MDkxNDA2MTU1MFoXDTI0MDkxNDA2MTU1MFowEDEOMAwGAlUEAxQFUEtJWCeW
WTATBgqhkJOPQIBBggqhkjOPQMBBwNCAATwoQsr863QrR0PoRIYQ96H7WykDePH
Wa0eVAE24bth43wCNC+U5aZ761dhGhSSJkVWRgVH5+prLlr+nzfiq+X4oxAwDjAM
BgNVHRMBAf8EAJAAMAKGByqGSM49BAEDRWAwRAIfMdkS5F631MnWVhi7uaKJzKCs
NnY/OKgBex6MIEAv2AIhAI2GdvfL+mGvhyPZE+JxRxWChmggb5/9eHdUcmW/jkOH
-----END X.509 CERTIFICATE-----
```

Figure 17: Non-standard 'X.509' Certificate Example

```
-----BEGIN NEW CERTIFICATE REQUEST-----
MIIBWDCCAQcCAQAwTjELMAkGAlUEBhMCU0UxJzAlBgNVBAoTHlNpbW9uIEpvc2Vm
c3Nvb2IuBEYXRha29uc3VsdCBQjEwMBQGA1UEAxMNam9zZWZzc29uLm9yZzBOMBAG
ByqGSM49AgEGBSuBBAAhAzoABLlPSkuXY0166MbxVJ3Mot5FCFuqQfn6dTs+9/CM
E0lSwVej77tj56kj9R/j9Q+LfysX8F09I5p3oGIwYAYJKoZIhvcNAQkOMVMwUTAY
BgNVHREEEETAPgg1qb3NlZnNzb24ub3JnMAAwGAlUdEwEB/wQCMAAwDwYDVR0PAQH/
BAUDAwegADAWBgNVHSUBAf8EDDAKBggrBgEFBQcDATAKBggqhkjOPQQDAgM/ADA8
AhxBvfhxPFfbBbsE1NoFmCUczOFApEuQVUw3ZP69AhwWXk3dgSUSknuwL5g/ftAY
dEQc8B8jAcnuOrfU
-----END NEW CERTIFICATE REQUEST-----
```

Figure 18: Non-standard 'NEW' PKCS #10 Example

```
-----BEGIN CERTIFICATE CHAIN-----
MIHjBgsqhkig9w0BCRABF6CB0zCB0AIBADFhol8CAQCgGwYJKoZihvcNAQUMMA4E
CLfrI6dr0gUWAgITiDAjBgsqhkig9w0BCRADCTAUBggqhkig9w0DBwQIZpECRWtz
u5kEGDCjerXY8odQ7EEERomZJvAurk/j81IrozBSBgkqhkiG9w0BBwEwMwYLKoZI
hvcNAQkQAw8wJDAUBggqhkig9w0DBwQI0tCBcU09nxEwDAYIKwYBBQUIAQIFAIAQ
OsYGYUFdAH0RNclp4VbKEAQUM2Xo8PMHBoYdqEcsbTodlCFAZH4=
-----END CERTIFICATE CHAIN-----
```

Figure 19: Non-standard 'CERTIFICATE CHAIN' Example

Appendix B. DER Expectations

This appendix is informative. Consult the respective standards for the normative rules.

DER is a restricted profile of BER [X.690]; thus, all DER encodings of data values are BER encodings, but just one of the BER encodings is the DER encoding for a data value. Canonical encoding matters when performing cryptographic operations; additionally, canonical encoding has certain efficiency advantages for parsers. There are three principal reasons to encode with DER:

1. A digital signature is (supposed to be) computed over the DER encoding of the semantic content, so providing anything other than the DER encoding is senseless. (In practice, an implementer might choose to have an implementation parse and digest the data as is, but this practice amounts to guesswork.)
2. In practice, cryptographic hashes are computed over the DER encoding for identification.
3. In practice, the content is small. DER always encodes data values in definite-length form (where the length is stated at the beginning of the encoding); thus, a parser can anticipate memory or resource usage up front.

Figure 20 matches the structures in this document with the particular reasons for DER encoding:

Sec.	Label	Reasons
-----+-----+-----		
5	CERTIFICATE	1 2 ~3
6	X509 CRL	1
7	CERTIFICATE REQUEST	1 ~3
8	PKCS7	*
9	CMS	*
10	PRIVATE KEY	3
11	ENCRYPTED PRIVATE KEY	3
12	ATTRIBUTE CERTIFICATE	1 ~3
13	PUBLIC KEY	2 3

Figure 20: Guide for DER Encoding

* Cryptographic Message Syntax is designed for content of any length; indefinite-length encoding enables one-pass processing (streaming) when generating the encoding. Only certain parts -- namely, signed and authenticated attributes -- need to be DER encoded.

~ Although not always "small", these encoded structures should not be particularly "large" (e.g., more than 16 kilobytes). The parser ought to be informed of large things up front in any event; this is yet another reason to DER encode these things in the first place.

Figure 20: Guide for DER Encoding

Acknowledgements

Peter Gutmann suggested to document labels for Attribute Certificates and PKCS #7 messages, and to add examples for the non-standard variants. Dr. Stephen Henson suggested distinguishing when BER versus DER is appropriate or necessary.

Authors' Addresses

Simon Josefsson
SJD AB
Johan Olof Wallins Vaeg 13
Solna 171 64
Sweden

EEmail: simon@josefsson.org
URI: <http://josefsson.org/>

Sean Leonard
Penango, Inc.
5900 Wilshire Boulevard
21st Floor
Los Angeles, CA 90036
United States

EEmail: dev+ietf@seantek.com
URI: <http://www.penango.com/>